



ANVER Item No.	Connection Thread Size	Thru Hole Dia. or Thread in. (mm)	Hex Size in. (mm)	L Height Added to Assembly in. (mm)	H Height in. (mm)
HS6-18M	M6 (6 mm) female to 1/8" NPT male	0.2 (5)	0.51 (13)	0.17 (4.3)	0.47 (12)
HS6-18M-G	M6 (6 mm) female to G1/8" male	0.2 (5)	0.56 (14)	0.22 (5.6)	0.51 (13)
HS6-14M	M6 (6 mm) female to 1/4" NPT male	0.2 (5)	0.63 (16)	0.22 (5.5)	0.63 (16)
HS6-14M-G	M6 (6 mm) female to G1/4" male	0.2 (5)	0.63 (16)	0.26 (6.4)	0.63 (16)
HS18-14M	1/8" NPT female to 1/4" NPT male	-	0.63 (16)	0.19 (4.8)	0.67 (17)
HS18-38M	1/8" NPT female to 3/8" NPT male	-	0.69 (17.5)	0.19 (4.8)	0.75 (19)
HS18-12M	1/8" NPT female to 1/2" NPT male	-	0.88 (22.4)	0.37 (9.5)	1.00 (25.4)
HS18-18M-G	1/8" NPT - female to G1/8" male	-	0.55 (14)	0.43 (11)	0.67 (17)
HS14-14M-G	1/4" NPT female to G1/4" male	-	0.67 (17)	0.56 (14)	0.87 (22)
HS14-38M	1/4" NPT female to 3/8" NPT male	-	-	0.12 (3)	0.87 (22)
HS38-38M-G	3/8" NPT female to G3/8" male	-	0.94 (24)	0.92 (24)	1.37 (35)
HS12-12M-G	1/2" NPT female to G1/2" male	-	1.12 (28)	1.18 (30)	1.70 (43)
HS34-34M-G	3/4" NPT female to G3/4" male	-	1.38 (35)	1.15 (29)	1.78 (45)