



Barbed Fittings which Push In from the Bottom for ANVER Universal Group 3 Suction Cups

- ANVER divides small universal vacuum suction cups into three groups based on mounting specifications and style. The Group 3 Fittings shown here are those that push in from the bottom, exposing a male thread at the top of the cup.
- Within each vacuum fitting group, the hardware is interchangeable with all other cups within the group. Any Group 3 fitting will fit any Group 3 cup.
- These all-metal, electro-less nickel-plated brass fittings are reusable. Once you buy the cups with fittings you only need to buy replacement rubber cups in the future.
- The cup is held from the bottom flange of the fitting which is screwed into a female connection above the cup to hold it tight. Replacement takes only a few seconds and requires that you unscrew the fitting, replace the cup, and screw the fitting back on. You can usually do this by hand, by grasping the rubber cup and fitting and turning. However, should you desire, you can also use a screw driver from below the cup.



ANVER Item No.	Connection Thread Size	Thru Hole Dia. in. (mm)	H Height in. (mm)
HS18	1/8" NPT male	0.23 (5.9)	1.14 (29)
HS18-SV-SS	1/8" NPT male	0.23 (5.9)	1.14 (29)
HS18-SV-LL	1/8" NPT male	0.23 (5.9)	1.14 (29)
HS18G	G 1/8" male	0.23 (5.9)	1.14 (29)
HS18-G-SV-SS	G 1/8" male	0.23 (5.9)	1.14 (29)
HS18-G-SV-LL	G 1/8" male	0.23 (5.9)	1.14 (29)