





Vacuum System Accessories






Tube Fittings for SLSA-2 Series Suspensions

Tube fittings are purchased separately to connect the spring loaded suspension assembly to the vacuum hose. They are available in barbed, push-in, and compression connections, with straight, elbow, and tee configurations. These fittings accept tubes with standard inside and outside diameters.

Barbed Fittings

| Fitting Type | ANVER Item No. | Connection Thread Size | Tube I.D. in. (mm) | Recommended Tubing Part No. | L in (mm) | H in. (mm) |
|--|----------------|------------------------|--------------------|-----------------------------|-----------|------------|
|  | BTC2-14S | 1/8" NPT | 0.175 (4.44) | PC-T14 | 0.55 (14) | 0.83 (21) |
| | BTC2-38S | 1/8" NPT | 1/4 (6.35) | - | 0.55 (14) | 1.10 (28) |
|  | BTC2-14E | 1/8" NPT | 0.175 (4.44) | PC-T14 | 0.63 (16) | 0.51 (13) |
| | BTC2-38E | 1/8" NPT | 1/4 (6.35) | - | 0.83 (21) | 0.51 (13) |
|  | BTC2-14T | 1/8" NPT | 0.175 (4.44) | PC-T14 | 1.26 (32) | 0.51 (13) |
| | BTC2-38T | 1/8" NPT | 1/4 (6.35) | - | 1.69 (43) | 0.51 (13) |
|  | BTC2-14BT | 1/8" NPT | 0.175 (4.44) | PC-T14 | 0.63 (16) | 0.83 (21) |
| | BTC2-38BT | 1/8" NPT | 1/4 (6.35) | - | 0.83 (21) | 1.10 (28) |

Push-In Fittings

| Fitting Type | ANVER Item No. | Connection Thread Size | Tube O.D. in. (mm) | Recommended Tubing Part No. | L in (mm) | H in. (mm) |
|---|----------------|------------------------|--------------------|-----------------------------|-----------|------------|
|  | PTC2-14S | 1/8" NPT | 1/4 (6.35) | PC-T14 | 0.51 (13) | 0.98 (25) |
| | PTC2-516S | 1/8" NPT | 5/16 (7.94) | - | 0.51 (13) | 1.14 (29) |
|  | PTC2-14E | 1/8" NPT | 1/4 (6.35) | PC-T14 | 1.18 (30) | 0.94 (24) |
| | PTC2-516E | 1/8" NPT | 5/16 (7.94) | - | 1.18 (30) | 1.06 (27) |
|  | PTC2-14T | 1/8" NPT | 1/4 (6.35) | PC-T14 | 1.42 (36) | 0.94 (24) |
| | PTC2-516T | 1/8" NPT | 5/16 (7.94) | - | 1.81 (46) | 1.18 (30) |



► This spec sheet was adapted for print from our website. Additional information and photos are available at www.anver.com. 4020301

Vacuum System Accessories



Tube Fittings for SLSA-2 Series Suspensions

Compression Fittings

| Fitting Type | ANVER Item No. | Connection Thread Size | Tube I.D. in. (mm) | Tube O.D. in. (mm) | Recommended Tubing Part No. | L in (mm) | H in. (mm) |
|---|----------------|------------------------|--------------------|--------------------|-----------------------------|-----------|------------|
|  | TC2-14S | 1/8" NPT | 0.175 (4.44) | 1/4 (6.35) | PC-T14 | 0.55 (14) | 1.02 (26) |
| | TC2-516S | 1/8" NPT | - | 5/16 (7.94) | - | 0.55 (14) | 1.02 (26) |
|  | TC2-14E | 1/8" NPT | 0.175 (4.44) | 1/4 (6.35) | PC-T14 | 1.18 (30) | 0.98 (25) |
| | TC2-516E | 1/8" NPT | - | 5/16 (7.94) | - | 1.18 (30) | 0.98 (25) |

► This spec sheet was adapted for print from our website. Additional information and photos are available at www.anver.com. 4020301