



ANVER's Large VP Series Vacuum Pads feature hand replaceable sealing rings and rugged high quality steel hubs making these some of the most versatile and economical vacuum cups available. Large VP Series Vacuum Cups can be mounted in a variety of ways.

Features:

- Economical - seals replace easily in minutes
- No tools needed
- Cleated bottoms for maximum capacity in both vertical and horizontal applications
- Short lip design for quick attach and release
- Heavy Duty steel hubs can be mounted in a variety of ways
- Vacuum Cup Materials:

The standard materials are Nitrile (NBR) and Silicone (SI).



Specifications for Large VP Series Vacuum Pads with Replaceable Seals:

Vacuum Pad Number	Replacement Seal Number	Mounting Type	Seal Dia. in (mm)	L in (mm)	W in (mm)	C in (mm)	D in (mm)	Vacuum Port NPT	H UNC	Shipping Weight lb (kg)	Capacity* lb (kg)
VP128Q-NBR	SR-128	Quad-Spring	13.25 (337)	5.66 (141)	5.66 (141)	0.42 (11)	1.42 (36)	3/8	M10 x 1.5	11 (5.0)	600 (272)
VP128Q-SI	SR-128-SI	Quad-Spring	13.25 (337)	5.66 (141)	5.66 (141)	0.42 (11)	1.42 (36)	3/8	M10 x 1.5	11 (5.0)	600 (272)
VP128S-NBR	SR-128	Ball-Swivel	13.25 (337)	—	—	0.42 (11)	2.44 (62)	3/8	—	12 (5.5)	600 (272)
VP128S-SI	SR-128-SI	Ball-Swivel	13.25 (337)	—	—	0.42 (11)	2.44 (62)	3/8	—	12 (5.5)	600 (272)
VP128C-NBR	SR-128	Clevis	13.25 (337)	—	—	0.42 (11)	2.92 (74)	3/8	—	13 (5.9)	600 (272)
VP128S-SI	SR-128-SI	Clevis	13.25 (337)	—	—	0.42 (11)	2.92 (74)	3/8	—	13 (5.9)	600 (272)

* Rated Load Capacity at 24 inch Hg vacuum when used in the horizontal plane based on a vacuum holding safety factor of two. Standard seal material is ANVER's exclusive non-marring blue Nitrile rubber (NBR). Silicone (SI) is also available.



VP Series Vacuum Pads

With Economical Snap-On Sealing Rings

Specifications for Large VP Series Vacuum Pads with Replaceable Seals:

Vacuum Pad Number	Replacement Seal Number	Mounting Type	Seal Dia. in (mm)	L in (mm)	W in (mm)	C in (mm)	D in (mm)	Vacuum Port NPT	H UNC	Shipping Weight lb (kg)	Capacity* lb (kg)
VP158Q-NBR	SR-158	Quad-Spring	16.25 (413)	6.5 (165)	4.0 (102)	0.44 (11)	2.13 (51)	1/2	3/4-10	25 (11.4)	1200 (544)
VP158Q-SI	SR-158-SI	Quad-Spring	16.25 (413)	6.5 (165)	4.0 (102)	0.44 (11)	2.13 (51)	1/2	3/4-10	25 (11.4)	1200 (544)
VP158S-NBR	SR-158	Quad-Spring**	16.25 (413)	9.0 (229)	4.0 (102)	0.44 (11)	2.13 (51)	1/2	3/4-10	25 (11.4)	1200 (544)
VP158S-SI	SR-158-SI	Quad-Spring*	16.25 (413)	9.0 (229)	4.0 (102)	0.44 (11)	2.13 (51)	1/2	3/4-10	25 (11.4)	1200 (544)
VP158C-NBR	SR-158	Clevis	16.25 (413)	—	—	0.44 (11)	3.94 (98)	1/2	—	26 (11.8)	1200 (544)
VP158S-SI	SR-158-SI	Clevis	16.25 (413)	—	—	0.44 (11)	3.94 (98)	1/2	—	26 (11.8)	1200 (544)

**For Use only on Suspension Assemblies for 5" x 7" Slides. Consult Factory.