



# Vacuum Cups and Suction Cups

## Generic P-Style / P Series EPDM Foam Vacuum Cups



### P Series EPDM (Ethylene-Propylene) Foam Vacuum Cups and Suction Cups

Ideal for use on plane surfaces, where minimum movement is required to maintain the pick-up area, and for support of pliable materials. Available in sizes from 0.65 to 6.13 inches (16.6 to 155.6mm).

Vacuum Cup Description and Part Number	Dimensional Drawing	Static* Diameter in. (mm)	Static* Height in. (mm)	Load Capacity at 24 in. Hg (609.6mm Hg) 2:1 safety factor lb (kg)
P-35 CUP & FITTING A-3350045		1.67 (42.5)	0.61 (15.5)	7.5 (3.4)
P-35 CUP & VALVE A-3350038		1.67 (42.5)	1.28 (32.5)	7.5 (3.4)
P-35 SEALING RING A-3350023		1.50 (38.0)	0.41 (10.5)	N/A
P-60 CUP & FITTING A-3350046		2.66 (67.5)	0.61 (15.5)	22.0 (10.0)
P-60 CUP & VALVE A-3350039		2.66 (67.5)	1.28 (32.5)	22.0 (10.0)
P-60 SEALING RING A-3350024		2.36 (60.0)	0.41 (10.5)	N/A

► This spec sheet was adapted for print from our website. Additional information and photos are available at [www.anver.com](http://www.anver.com). 3002601

# Vacuum Cups and Suction Cups



## Generic P-Style / P Series EPDM Foam Vacuum Cups

Vacuum Cup Description and Part Number	Dimensional Drawing	Static* Dia. in. (mm)	Static* Height in. (mm)	Load Capacity at 24 in. Hg (609.6mm Hg) 2:1 safety factor lb (kg)
P-100 CUP & FITTING A-3350047		4.23 (107.5)	0.75 (19.0)	65.0 (29.5)
P-100 CUP & VALVE A-3350040		4.23 (107.5)	2.01 (51.0)	65.0 (29.5)
P-100 SEALING RING A-3350025		3.94 (100.0)	0.41 (10.5)	N/A
P-200 CUP & FITTING A-3350048		8.46 (215.0)	1.34 (34.0)	275 (124.7)
P-200 SEALING RING A-3350026		8.27 (210.0)	1.04 (26.5)	N/A
P-300 CUP & FITTING A-3350049		12.40 (315.0)	1.34 (34.0)	600 (272.2)
P-300 SEALING RING A-3350027		12.20 (310.0)	1.04 (26.5)	N/A
OP-20X100 CUP & SEAL A-3350050		4.37 [L] 1.19 [W] (111.0 [L] 30.1 [W])	0.71 (18.0)	21 (9.5)
OP-20X100 SEALING RING A-3350028		4.20 [L] 1.16 [W] (106.7 [L] 29.4 [W])	0.41 (10.4)	N/A



# Vacuum Cups and Suction Cups

## Generic P-Style / P Series EPDM Foam Vacuum Cups

VacuumCup Description and Part Number	Dimensional Drawing	Static* Dia. in. (mm)	Static* Height in. (mm)	Load Capacity at 24 in. Hg (609.6mm Hg) 2:1 safety factor lb (kg)
OP-40X200 CUP & SEAL A-3150051		8.25 [L] 1.97 [W] (210.0 [L] 50.0) [W]	0.85 (21.4)	70 (31.8)
OP-40X200 SEALING RING A-3350029		8.13 [L] 1.89 [W] (207.0 [L] 47.8) [W]	0.41 (10.4)	N/A

► This spec sheet was adapted for print from our website. Additional information and photos are available at [www.anver.com](http://www.anver.com). 3002601